

Reproduced from Ordnance Survey digital map data ©Crown copyright

The site is to be cleared of all rubbish, undergrowth and unwanted matter. Vegetable matter shall be stripped and any roots grubbed up. All material to be disposed to a tip provided by the Contractor

Unless laboratory information states otherwise, all existing carriageway construction is deemed to

The Contractor will be responsible for all necessary dewatering and trench support to execute the work in a satisfactory manner and will be deemed to have included for the same within their price.

During construction, if bituminous layers are trafficked or become contaminated prior to the next layer being laid, a bond coat must be applied. A bond coat shall be applied prior to the laying of a new

Bitumen emulsion bond coats to conform to BS EN 13108 with minimum cohesion in accordance with BS EN 13808:2013, Table 4, Class 4. The bond coat shall have BBA/HAPAS accreditations and

The depiction of any service apparatus on this or any other drawing has been obtained from third party sources and is not necessarily accurate or complete. At no time does the inferred position on the drawing absolve the Contractor from taking all necessary steps to locate service apparatus in accordance with the methods suggested by the highway authority. The Developer and Engineer will accept no claims whatsoever in respect of any losses or damage caused in respect of such apparatus,

The Contractor shall be deemed to have allowed for locating of service apparatus by hand digging in

Е	Updated to suit latest infrastructure layout	26.05.22	PCB	LAM
D	Updated to suit latest infrastructure layout	20:05:22	LAM	LAM
С	Infrastructure footways updated	19:04:22	LAM	LAM
В	Amended to suit latest infrastructure layout	21:03:22	LAM	LAM
Α	Revised to suit the latest design. Bus stops and tactiles added	07:05:21	AG	PMW
Rev	Description	Date	Drawn	Checked

Wormald Burrows Partnership Ltd

E3838/704/E

1:500 @ A1

